





APPLIANCE DIMENSIONS




CABINET/COUNTERTOP DIMENSIONS

10" (25.4CM) TO COMBUSTIBLE SIDE WALL MIN. BOTH SIDES



CABINET / COUNTERTOP DIMENSIONS - FRONT VIEW


*NOTE: PRODUCT TOLERANCE +/- 1/16" (+/- 1.6MM)-o UNLESS OTHERWISE NOTED



CABINET/COUNTERTOP CUTOUT DIMENSIONS WITH DOWNDRAFT VENT - TOP VIEW.

48"

A - CUTOUT WIDTH	48" (121.9CM)
B - HOLE OFFSET	20 13/16" (52.9CM)
C - DOWNDRAFT VENT CUTOUT	43 1/2" (110.5CM)
APPROVED DOWNDRAFT VENT MODELS	MRV48




CABINET/COUNTERTOP CUTOUT DIMENSIONS WITH DOWNDRAFT VENT - SIDE VIEW

NOTE: Gas and electrical connections may only be routed through the bottom of the rangetop when installed with a downdraft vent.

dacor

48-INCH GAS RANGETOP

CABINET/COUNTERTOP CUTOUT DIMENSIONS




CABINET/COUNTERTOP CUTOUT DIMENSIONS WITHOUT DOWNDRAFT VENT - TOP VIEW

48"

A - CUTOUT WIDTH	48" (121.9CM)
B - HOLE OFFSET	20 13/16" (52.9CM)

CLEARANCE DIMENSIONS



48"

A - CUTOUT WIDTH	48" (121.9CM)
B	48" (121.9CM)* MINIMUM 54" (137.2CM)** RECOMMENDED

NOTE: All vertical clearances must be maintained for a minimum of 18" (457mm) above the cooking surface.


DHD48987W

48-INCH WALL HOOD

MODERNIST COLLECTION




APPLIANCE DIMENSIONS




	A	B	C	D
48"	47 7/8" (121.6cm)	24" (61cm)	18" (45.7cm)	11 7/8" (30.2cm)

TOP ELECTRICAL ACCESS DIMENSIONS




	A	B	C
48"	1 1/2" (3.81cm)	5" (12.7cm)	3" (7.62cm)

REAR ELECTRICAL ACCESS DIMENSIONS



	A	B	C
48"	1" (2.54cm)	5" (12.7cm)	3" (7.62cm)

CABINET LAYOUT DIMENSIONS




MINIMUM WIDTH OF "E"	
	E
48"	48" (121.9cm)

CLEARANCES AND DIMENSIONS

- Dimensions that are shown in Figure 1 (for 24") or Figures 4 and 5 (for 30") must be used. Given dimensions provide minimum clearance. Locate electrical outlet in the shaded area in the upper left-hand corner of the cutout. See Figure 9.
- Contact surface must be solid and level. Pay special attention to the floor on which the Microwave Drawer will sit. The floor of the opening should be constructed of plywood strong enough to support the weight of the oven (about 100 pounds).
- Check location where the Microwave Drawer will be installed for proper electrical supply.


- Your oven can be built into a cabinet or wall by itself or under a gas or electric wall oven.
- Be sure that the clearance of the floor between the wall oven and the microwave drawer is a minimum of 2-inches.
- The microwave interior will easily accommodate a 9" x 13" oblong dish or a bag of microwave popcorn.
- The oven can also be mounted flush. Please see instructions for flush mounting included with the Flush Mount Deflector vent.

24" MICROWAVE DRAWER MEASUREMENTS

**Figure 1**

Cutout Dimension 22 1/8" x 15 9/16"

- A. 6"
- B. Suggested electrical outlet location*
- C. Anti-Tip block
- D. 5"
- E. 3-1/2"
- F. 4"
- G. 22-1/8" opening
- H. 14-13/16" to bottom of Anti-Tip block
- I. Allow 7/8" overlap
- J. 23-1/2" minimum depth
- K. Allow 3/16" overlap
- L. 36" countertop height
- M. Allow 7/16" minimum overlap
- N. Floor must support 100 lb
- O. 24" cabinet minimum
- P. 15-9/16" opening
- Q. Allow 1/8" overlap

**Figure 2**

- A. 21-5/8"
- B. 4-11/16"
- C. 1-3/4"
- D. 21-7/8"
- E. 23-7/8"
- F. 15-7/8"
- G. 14-19/32"
- H. 1-9/64" door thickness
- I. 15" auto drawer opening
- J. 4"

Figures 1 and 2 contain many Microwave Drawer measurements for reference when planning the drawer's location.

This Microwave Drawer can be installed below any electric or gas wall oven.

* Can also be installed using an electrical outlet in an adjacent cabinet within the area where the provided electrical cord can reach. Power cord access hole in cabinet should be a minimum 1 1/2" diameter hole and deburred of all sharp edges.

IMPORTANT Always allow sufficient power cord length to the electrical outlet to prevent tension.

Always check electrical codes for requirements.

This drawing represents a typical standard cabinet. If installed in custom cabinets with extended counter tops, take into account visibility and access to controls. See Figure 3.





Figure 3


- A. 25"
- B. 1/2" minimum
- C. 15-7/8"
- D. 36"
- E. Control panel shown in open position
- F. 24"
- G. 34-1/2"

DETAILED PLANNING DIMENSIONS


15" ICE MACHINES

KUIX335H/ **KUIX535H** – D 24" x W 14⁴⁵/₆₄" x H 34⁴⁵/₆₄" (depth without handle)

PRODUCT DIMENSIONS



MODEL #		KUIX335H, KUIX535H	
		in	cm
A	Width	14 ⁴⁵ / ₆₄	37.33
B	Width of grille	14 ⁵⁵ / ₆₄	37.71
C	Height to top of handle	31 ¹⁵ / ₃₂	79.93
D	Height of door	30 ⁵¹ / ₆₄	76.4
E	Height of grille	3 ²⁹ / ₃₂	9.93
F	Width of recessed ice machine	14 ²⁹ / ₃₂	37.81
G	Depth without door	21 ²¹ / ₃₂	55.02
H	Depth with door	23 ²⁵ / ₃₂	60.42
I	Depth with handle	26 ¹⁷ / ₆₄	66.7



IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All KitchenAid® appliances are appropriately UL, CUL or CSA approved.

KitchenAid®


DETAILED PLANNING DIMENSIONS

15" ICE MACHINES

KUIX335H/ KUIX535H – D 24" x W 14⁴⁵/₆₄" x H 34⁴⁵/₆₄" (depth without handle)

MODEL #		KUIX335H, KUIX535H	
		in	cm
A*	Height to top of door (min.)	34 ⁶¹ / ₆₄	86.23
B*	Height to top of handle (min.)	31 ⁷ / ₁₆	79.83
C*	Height to top of grille (min.)	3 ⁷ / ₈	9.83
D*	Height of recessed ice machine (min.)	33 ³⁵ / ₆₄	85.23
E	Depth with door open 90° (min.)	39 ¹ / ₈	99.39
F	Depth with handle (min.)	26 ¹⁷ / ₆₄	66.72
G	Depth with door (min.)	23 ¹³ / ₁₆	60.47
H	Depth without door (min.)	21 ³³ / ₆₄	54.67
I	Depth of grille (min.)	19 ⁶¹ / ₆₄	50.67

* Add 1" (2.5 cm) to the height dimension when leveling legs are fully extended.



IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All KitchenAid® appliances are appropriately UL, CUL or CSA approved.

KitchenAid®


DETAILED PLANNING DIMENSIONS

15" ICE MACHINES

3 of 3

KUIX335H/ KUIX535H – D 24" x W 14⁴⁵/₆₄" x H 34⁴⁵/₆₄" (depth without handle)

OPENING/CLEARANCE DIMENSIONS



MODEL #		KUIX335H, KUIX535H	
		in	cm
A*	Width (min.)	15	38.1
	Width without hinge side spacer option (min.)	15	38.1
	Width with hinge side spacer option (min.)	15 ³ / ₄	40.0*
B*	Width of outlet location	6	15.0
C*	Outlet location – distance from side	1	2.5
D*	Width of water connection location	3 ¹ / ₂	8.9
E	Minimum width from hinged side of ice machine to fixed wall – door open 90°	2	5.1
	Minimum width from hinged side of ice machine to fixed wall – door fully open 180°	13 ¹ / ₄	33.7
	Minimum width from hinged side of ice machine to fixed wall – door fully open 118°	6 ⁷ / ₈	17.4
F	Height (min.)	34	86.4
G	Height of outlet location	8	20.3
H	Height of water connection location	9	22.9
I	Outlet location – distance from bottom	12	30.5
J	Depth of cabinet (min.)	24	61.0
K	Water line location – distance from side	2 ³³ / ₆₄	6.41
L	Power supply – distance from side	3 ⁴⁹ / ₆₄	9.58
M	Drain hose – distance from side	7 ⁵ / ₁₆	18.57
N	Power supply – distance from bottom	1 ¹ / ₄	3.17
O	Drain hose – distance from bottom	2 ⁴³ / ₆₄	6.79
P	Water line location – distance from bottom	11 ⁹ / ₁₆	29.38
e	Recommended electrical connection location		
w	Recommended water connection location		

* Install 3/4" (1.9 cm) front hinge-side spacer flush with face of adjacent cabinet and 3/4" (1.9 cm) back hinge-side spacer 6" (15.2 cm) from back wall.

ELECTRICAL REQUIREMENTS

115 V, 60 Hz, AC only, 15 or 20 A fused, grounded circuit is required. A dedicated circuit is recommended. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

WATER PRESSURE REQUIREMENTS

A cold water supply with water pressure between 30 and 120 psi (207 and 827 kPa) is required to operate the ice maker. Call a licensed, qualified plumber with any questions about the water pressure.

Reverse Osmosis Water Supply

IMPORTANT: The use of a reverse osmosis system with this product is not recommended. However if you do use reverse osmosis, follow these instructions.

IMPORTANT: The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the ice machine needs to be between 30 and 120 psi (207 and 827 kPa). If a reverse osmosis water filtration system is connected to the cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

IMPORTANT: Dimensional specifications are provided for planning purposes only.

Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All KitchenAid® appliances are appropriately UL, CUL or CSA approved.

W11349805A

®/TM ©2019 KitchenAid. All rights reserved.

In some European factories the letter "W" of the part code mentioned herein will be automatically replaced by the number "4000" (e.g. "W12345678" becomes "400012345678")

KitchenAid®

03/19

MODEL




Single Zone Beverage Cooler
Black Stainless SteelPRB24C01BBSG **x2**

Size	24"
Dimensions	23-7/8"W x 33-7/8"H x 23-5/8"D
Weight	112lbs.
Installation Type	Compact / Built-in / Freestanding
Refrigerant Type	R600a

FEATURES

Capacity	13 bottles (750 ml), 84 12oz cans or 7 bottles (750 ml), 112 12oz cans
Volume	5.6 cu/ft
Temperature Range	34° - 50° F
Sound Level	39 dBA
Door Finish	Black Stainless + Glass
Cabinet Finish	Black
Interior Finish	Black
Field-Reversible Door	Yes
Zero-Clearance Door Hinge	Yes
Door Glass	Dual-pane, Low-e Argon-filled*
Shelving - Wood	1 full-extension, black wood rack w/ black stainless trim
Shelving - Beverage	2 adjustable, transparent-gray glass shelves w/ airflow openings
Controls	Electronic Capacitive Touch
Lighting	3-Color LED Cloud White, Deep Blue, Amber
Door Open Alarm	Yes, after 3 minutes
Sabbath Mode	Yes
Air Filtration	Yes, w/ carbon filter
PreciseTemp™	Yes
Active Cooling Technology	Yes
Vibration Dampening System	Yes

AC POWER 115V, 60Hz at Max. 1.5A

WARRANTY 2 years parts, 5 years compressor
1 year labor

*Dual-pane, argon-filled glass improves insulation to minimize heat exchange and increases soundproofing characteristics. The Low-e coating helps minimize the amount of UV and infrared light that passes through the glass door.

Transforming the Kitchen through Design, Discovery, and Care

Specifications subject to change, check zephyronline.com for up-to-date information.
Zephyr | 2277 Harbor Bay Parkway, Alameda, CA 94502 | 888.880.8368

MAY20.0201



23 cu. ft. 4-Door Flex




MODEL RF23M8070 DIMENSIONS

#RF23M8070SG

SAMSUNG


Be sure your new fridge will fit

Don't wait until delivery to be sure your new refrigerator will fit – both in your kitchen and through all doorways. This guide includes all pertinent measurements and clearances so you can buy with confidence.



Counter-Depth Refrigerator

Counter-depth models sit flush with your kitchen cabinets for a premium, built-in look. They are perfect for galley and island kitchens where space is limited.



Installation clearances

- ✓ Allow 3.75" of clearance when installing along a wall. This will allow for the door to open 90 degrees without the handle contacting the wall. 50
- ✓ Allow 2" minimum clearance at rear for proper air circulation and water/electrical connections. 50
- ✓ Allow a 5/8" minimum clearance at sides and top for ease of installation. 10

For optimal usage and ability to open refrigerator doors completely, do not install next to a wall.

Please note: The above dimension and cutout information is for planning purposes only. For complete installation details, consult manual packed with product, or download manual online at samsung.com.



Walk the delivery route

- ✓ Identify the narrowest opening that the appliance will travel, from outside the home to the location where it will be installed.
- ✓ Appliance depth or width must be smaller than the width of the narrowest opening.

WARMING DRAWER DIMENSIONS

(A) Chassis Face Width	(B) Chassis Width	(C) Chassis Depth	(D) Drawer Depth (without panel)	(D) Drawer Depth (with panel)	(E) Chassis Height (with feet)
29 5/8" (75.2 cm)	27 7/8" (70.8 cm)	20 15/16" (53.1 cm)	19 3/32" (48.5 cm)	19 27/32" (50.4 cm)	9 3/4" (24.8 cm)




Overall dimensions (top)






Chassis(drawer removed)

CUTOUT DIMENSIONS

(A) Cutout Width	(B) Min. Width to Adjacent Doors/Drawer	(C) Cutout Height	(D1) Min. Vertical Gap Betw. Warming Drawer Cutouts	(D2) Min. Vertical Gap Betw. Dacor Wall Oven	(E1)* Flush to Drawer Front	(E2)** Flush to Cab't Frame / Drawer with Panel Flush to Drawer Front	(E3) Drawer with Panel Flush to Cab't Frame	(E4) Drawer with Oversized Panel	(F) Min. Width Inside Cleats	(G) Min. Cutout Depth
30 1/4" (76.8 cm)	30 1/4" (76.8 cm)	10 1/2" (26.7 cm)	1 1/4" (3.2 cm)	1 1/2" (3.8 cm)	15 5/64" (2.7 cm)	15 3/64" (4.6 cm)	2 37/64" (6.5 cm)	1 37/64" (4.0 cm)	28" (71.0 cm)	E1: 24" (61.0 cm); E2: 24 7/8" (63.2 cm) to 25" (63.5 cm)



Section AA (left-side view)





Section BB (front view)



*Dimension with 11/16" in. (1.75 cm) appliance face to cabinet frame face; adjust (E1) depth for a different cabinet

**Requires cabinet depth dimension "G" to be 24 3/4" (62.9 cm)



PANEL DIMENSIONS



Drawer for WIP Model without Front Panel



Drawer for WIP Model with Front Panel Attached



Drawer for WIM and WIS Models

NV51T5511D

30" Double Wall Oven


SAMSUNG

Cabinet Dimensions

Double Oven Installed in Cabinet

*Junction Box

**Allow a minimum of 22" for clearance to adjacent corners, drawers, walls, etc. when door is open.



Total Capacity: 5.1/5.1 cu. ft.

Upper Oven: 5.1 cu. ft.

Lower Oven: 5.1 cu. ft.

- Hidden Bake Element
- Bake: 175°F–550°F
- Broil: Low-High
- Proofing
- Sabbath Mode

Warranty

One (1) Year All Parts and Labor

Product Dimensions & Weight (WxHxD)

Outside (Max) Wall Oven Dimensions: 29³/₄" x 51¹/₂" x 26⁵/₈"

Wall Oven Cut-Out Dimensions: 28¹/₂" x 50¹/₄" x 23¹/₂"

Weight: 236.3 lbs

Shipping Dimensions & Weight (WxHxD)

Dimensions: 33¹¹/₁₆" x 56³/₈" x 29¹³/₁₆"

Weight: 265.2 lbs

Color

Stainless Steel

Model

NV51T5511DS/AA

UPC Code

887276384986


Fingerprint Resistant

Black Stainless Steel

NV51T5511DG/AA

887276384979

Product Dimensions



KW RATING

240V	8.9 kW
208V	6.7 kW

BREAKER SIZE

240V	40 Amps
208V	40 Amps

Actual color may vary. Design, specifications, and color availability are subject to change without notice. Non-metric weights and measurements are approximate.

©2020 Samsung Electronics America, Inc. 85 Challenger Road, Ridgefield Park, NJ 07660. Tel: 800-SAMSUNG. samsung.com. Samsung is a registered trademark of Samsung Electronics Co. Ltd.